

# WEBEL TECHNOLOGY LIMITED

## CORRIGENDUM – II

**Tender No. WTL/NKGS/ICCC/20-21/024 dated 26.02.2021**

Section No.	Clause No.	Page No.	Queries	WTL Replies
ICCC/TR/39.01 // Technical Requirements for ICC // 38. Local Application Buffer NAS		122	<ul style="list-style-type: none"><li>• 32 Core, 27M Cache, Turbo, HT (150W) DDR4-2666</li><li>• 2666MT/s RDIMMs</li><li>• Performance Optimized</li><li>• 128GB RDIMM 2666MT/s Dual Rank</li><li>• No Additional Processor</li><li>• iDRAC9,Enterprise</li><li>• 192TB 7.2K RPM NLSAS 12Gbps 512e 3.5in Hot-plug Hard Drive</li><li>• PERC H730P RAID Controller, 2GB NV Cache, Mini card</li><li>• Jumper Cord,10A,2M,C13/C14 (India BIS)</li><li>• Dual, Hot-plug, Redundant Power Supply (1+1), 1100W</li><li>• Trusted Platform Module 1.2</li><li>• Broadcom 57416 Dual Port 10GbE BASE-T &amp; 5720 Dual Port 1GbE BASE-T, rNDC</li><li>• Redhat OS</li><li>• RAID 5</li></ul>	<ul style="list-style-type: none"><li>• iDRAC9 /iLO• 32 Core, 27M Cache, Turbo, HT (150W) DDR4-2666</li><li>• 2666MT/s RDIMMs</li><li>• Performance Optimized</li><li>• 128GB RDIMM 2666MT/s Dual Rank</li><li>• No Additional Processor</li><li>• iDRAC9/iLO, Enterprise</li><li>• 192TB 7.2K RPM NLSAS 12Gbps 512e Hot-plug Hard Drive</li><li>• RAID Controller, 2GB NV Cache, Mini card</li><li>• Jumper Cord,10A,2M,C13/C14 (India BIS)</li><li>• Dual, Hot-plug, Redundant Power Supply (1+1), 1100W</li><li>• Trusted Platform Module 1.2</li><li>• Dual Port 10GbE BASE-T &amp; 5720 Dual Port 1GbE BASE-T, rNDC</li><li>• Redhat OS</li><li>• RAID 5</li></ul>